

# **SL20-23 SLIDELOCK™ REEL TRAILER SPECS**



## **EXCLUSIVE STANDARD ADDED VALUE:**

- SLIDELOCK™ Technology Provides Industry Leading Safety, Ease of Use, Low Maintenance and Durability.
  - SAFETY and Peace of Mind
  - No Pins, Cotters, or Lanyards that Secure the Reel Arbor (which is the most critical safety point).
  - Faster Reel Loading, Unloading, and Deployment Reduces Labor Costs and Fatigue on Workers.

BUILT FOR SAFETY. BUILT FOR SPEED. BUILT TO LAST.

CAPACITIES: 22,100 lbs. GVWR @ 15% Tongue Weight

**AXLES**: Tandem 10K lbs. Sprung

WHEELS: (4) 17.50 x 6.75 HC / 8 on 6.5 BC w/ 0.19 Inset

**TIRES**: (4) ST-215/75R17 LR-H Tires

BRAKES: 12.25" x 3.38" Electric w/ Safety Breakaway Kit

PAYLOAD: ALL FINAL PAYLOADS BASED ON CHOSEN MODEL AND OPTIONS

REEL CAPACITY:

(2x) 120" Diameter x 62" Width x 7,700 lbs.

or

(3x) 96" Diameter x 62" Width x 5,100 lbs.

**REEL SHAFT DIAMETER:** 2.50" Tube w/ Centering Collars

**OVERALL LENGTH**: 367.25"

**OVERALL WIDTH: 100.75"** 

**OVERALL WEIGHT**: 6,400 lbs. Approx.

(Actual Trailer Weight will Vary with Options & Finishes Chosen)

## **STANDARD FEATURES**

- SLIDELOCK Technology Provides Industry Leading Safety, Ease of Use, Low Maintenance and Durability.
- Oil Bath Hubs (Greaseable Option All)
- Electric Brakes
- Wheel Chock Holders

## STANDARD TRAILER BODY

- Heavy Duty 6" X 3" X ¼"
- 6-Position Adjustable Hitch
- 1/2" X 36" GR70 Yellow Zinc Safety Chains with Hooks
- 12,000 lbs. Static Front Jack w/ Spring Return
- Ground Lug: Copper Alloy Bolted to Frame
- Fenders: 1/8" Tread Plate
- A-frame: Approx. 6' Long
- Grip Strut Catwalks

#### **WIRING**

- DOT / ICC Approved LED Lights and Conspicuity Reflective Tape
- FMVSS / CMVSS Standard 108 LED Lighting
- Sealed Beam, Rubber Mounted Stop, Turn, Tail and Marker Lights
- 100% Sealed Heat-Shrinked Wiring Connections w/ Full Loom
- Breakaway Kit with Absorbed Glass Mat (AGM) Battery

### **PAINT**

- Biodegradable Pretreat Acid Cleaning
  (Superior to re-used sandblasting material that can impregnate metals with oil)
- Seams Caulked
- Rust Preventative 2-Part Epoxy Primer
- Standard Colors: Red, Black, White and CAT Yellow

### **OPTIONS**

- 10-Year Galvanized Structural Warranty (2-Year Painted)
- 16" Long 6-Bolt Hitch Extension (w/ 52" Safety Chains and Breakaway Cable Extension)
- Aluminum or Steel Toolbox
- Wiring Connections Soldered and Sealed w/ Heat Shrink Tubing
- Plug-and-Play Sealco Wiring Harness
- Wheel Chocks: Rubber or All Weather Galvanized Grip Strut
- Spare Tire and Mount
- Solar Charged Breakaway Kit
- Strobe Warning Lights
- All Stainless Steel Fasteners (1/2" and under)
- Truck-Lite Lighting
- Lug Nut Indicators

